

CONTAINERS SPECIFICATIONS

Standard						Special				Refrigerated		
20'	40'	40'HC	45'	48'	53'	20' Open Top	40' Open Top	20' Collapsible Flat RackOpen Top	40' Collapsible Flat RackOpen Top	20' Muffler Grade Stainless Steel Reefer	40' HC Grade Stainless Steel Reefer	40' HC Aluminium Reefer



Characteristics

Capacity	33 m3 1,170cft	67.7m3 2,391cft	76.40m3 2,700cft	86.5m3 3,055cft	98.880m3 3,489cft	108.600m3 3,835cmb	33.200m3 1,130cft	65.5m3 2,306cft	x	x	28.300m3 999cft	67.700cbm 2,391cft	67.500cbm 2,384cft
Weight Payload	22,850kgs-28,160kgs 48,171lb-62,082lb	26,760kgs-28,760kgs 58,996lb-63,405lb	26,750kgs-28,550kgs 58,974lb-62,942lb	28,280kg 62,350lb	25,340kg 56,350lb	x	28,230kg 62,240lb	26,580kg 58,602lb	31,260kg 68,917lb	31,260kg - 40,050kg 68,917lb-88,300lb	27,450kg 60,517lb	29,190kg 64,353lb	28,760kg 63,405lb
Tare Weight	2,150kg-2,220kgs 4,740lb-4,894lb	3,720kg-3,740kgs 8,201lb-8,245lb	3,730kg-3,750kgs 8,223lb-8,708lb	4,740kg 10,450lb	5,140kg 10,865lb	x	2,250kg 4,960lb	3,900kg 8,598lb	2,740kg 6,041lb	2,600kg - 2,820kg 5,732lb - 6,217lb	3,030kg 6,680lb	4,810kg 10,604lb	4,260kg 9,392lb
Max. Gross Weight	24,000kgs-30,480kgs 52,911lb-67,197lb	30,480kgs-32,500kgs 67,197lb-71,650lb	30,480kgs-32,500kgs 67,197lb-71,650lb	33,020kg 72,800lb	30,480kg 67,197lb	x	30,480kgs 67,200lb	30,480kg 67,200lb	34,000kg 74,957lb	30,000kg - 45,000kg 66,140lb -99,210lb	30,480kg 67,197lb	34,000kg 74,957lb	33,020kg 72,797lb
Internal Length	5.898m 19'4"	12.032m 39'6"	12.033m 39'6"	13.556m 44'6"	14.470m 47'6"	15.994m 52'-5 11/16"	5.900m 19'4"	12.040m 39'6"	6.040m 19'10"	12.054m 39'7"	5.446m 17'10"	11.583m 38'	11.583m 38'
Internal Width	2.352m 7'9"	2.352m 7'9"	2.352m 7'9"	2.352m 7'9"	2.505m 8'3"	2.505m 8'- 2 5/8"	2.350m 7'8"	2.350m 7'8"	2.230m 7'4"	2.230m 7'4"	2.294m 7'6"	2.294m 7'6"	2.294m 7'6"
Internal Height	2.392m 7'10"	2.392m 7'10"	2.698m 8'10"	2.701m 8'10"	2.726m 8'11"	2.71m 8'- 10 11/16"	2.310m 7'7"	2.310m 7'7"	2.230m 7'4"	1.955m 6'5"	2.263m 7'5"	2.548m 8'4"	2.548m 8'4"
Door Opening Width	2.340m 7'8"	2.340m 7'8"	2.340m 7'8"	2.340m 7'8"	2.493m 8'2"	2.493m 8'- 2 1/8"	2.220m 7'3"	2.340m 7'8"	x	x	2.591m 8'6"	2.290m 7'6"	2.290m 7'6"
Door Opening Height	2.280m 7'6"	2.280m 7'6"	2.585m 8'6"	2.5880m 8'6"	2.691m 8'10"	2.597m 8'- 6' 1/4"	2.260m 7'5"	2.260m 7'5"	x	x	2.260m 7'5"	2.572m 8'5"	2.500m 8'3"
Roof Opening Length							5.500m 18'1"	11.600m 38'1"	x	x	x	x	x
Roof Opening Width							2.220m 7'3"	2.140m 7'	x	x	x	x	x
External Length									6.058m 19'11"	12.192 m 40'	6.058m 19'11"	12,192m 40'	12,192m 40'
External Width									2.438m 8'	2.438m 8'	2.438m 8'	2.438m 8'	2.438m 8'
External Height									2.591m 8'6"	2.591m 8'6"	2.591m 8'6"	2.896m 9'6"	2.896m 9'6"
Cooling Unit											8,820kcal/h at 35F	8,820kcal/h at 35F	8,820kcal/h at 35F
Controlled Atmosphere											yes	yes	yes
Dehumidification											yes	yes	yes